

HOME

MAGNETIC CYCLE



PEC-3200 Owner's manual STEP 1: ATTACH BOTH STABILIZERS (02 + 2a) TO MAIN FRAME (01). FIX WITH BOLTS (27) AND WASHERS (31).

STEP 2:

IMPORTANT: READ ALL STEPS BEFORE ATTACHING PEDALS.

- a. ASSEMBLE PEDAL STRAPS TO PEDALS. (STRAP MARKED "L" TO THE LEFT PEDAL, STRAP MARKED "R" TO THE RIGHT PEDAL).
- b. ATTACH PEDALS (17 & 18) TO PEDAL CRANKS, (PEDALS MARKED "L" AND "R" INDICATES LEFT AND RIGHT SIDE OF BIKE. MAKE SURE NOT TO MIX IT UP).
- c. LEFT PEDAL HAS LEFTHAND THREAD AND MUST BE TURNED COUNTERCLOCKWISE (CCW) TO ATTACH, RIGHT PEDAL HAS RIGHTHAND THREAD, MUST BE TURNED CLOCKWISE (CW) TO ATTACH.
- STEP 3: ATTACH SADDLE (12) TO SADDLE PLATE OF SEAT POST (03). FASTEN IT WITH SPRING WASHERS (33) AND NYLON NUTS (34).
- STEP 4: SLIDE SEAT POST INTO THE SEAT POST BOOT (13) THEN ATTACH SEAT POST (03) TO MAIN FRAME, ADJUST SADDLE TO DESIRED HEIGHT AND TIGHTEN WITH KNOB (26).
- STEP 5: INSERT TENSION CABLE (09) INSIDE OF HANDLEBAR POST (04), PULL THE (04) TENSION CABLE OUT OF MIDDLE HOLE OF HANDLEBAR POST.

CONNECT WIRE (A) (10) AND WIRE (B) (11), THEN ATTACH HANDLEBAR POST TO MAIN FRAME (01), FIX WITH WASHERS (31) AND BOLTS (28).

ASSEMBLE TENSION CONTROL (08) AND TENSION CABLE (09), (REFER TO DIAGRAM), PULL THE UPPER CABLE OF TENSION CONTROL (08) FROM MIDDLE HOLE TO TOP HOLE OF THE HANDLBAR POST (04)


INSERT THE TENSION CONTROL (08) ONTO HANDLEBAR POST (04), TIGHTEN WITH SCREW (29).

- STEP 6: ASSEMBLE HANDLEBAR (05) ONTO HANDLEBAR POST (04), FIX WITH WASHER (32) AND T-KNOB (25), THEN ASSEMBLE FOAM GRIPS (16) AND CAPS (15) ONTO HANDLEBAR.
- STEP 7: CONNECT WIRE (A) (10) ONTO MONITOR (07), THEN ATTACH MONITOR ON THE PLATE OF HANDLEBAR POST WITH SCREW (35).

NOW YOUR PEC-3200 HAS BEEN WELL ASSEMBLED.

" THE BATTERIES MUST BE REMOVED FROM THE APPLIANCE BEFORE IT IS SCRAPPED AND THAT THEY ARE DISPOSED OF SAFELY ".

NOTE: WHILE ASSEMBLE FOAM GRIP (16) ONTO HANDLEBAR (05), USE SOME SOAP WATER FOR LUBRICANT.



KEY.	Q'TY	DESCRIPTION	
01.	1	MAIN FRAME	
02.	1	STABILIZER	
2a.	1	FRONT REAR STABILIZER	
03.	1	SEAT POST	
04.	1	HANDLEBAR POST	
05.	1	HANDLEBAR	
06.	1	CRANK ASSEMBLY	
07.	1	CYCLEMONITOR	
. 08.	1	TENSION CONTROL	
09.	1	TENSION CABLE	
10.	1	WRE (A)	
11.	1	WIRE (B)	
12.	1	SADDLE	
13.	1	SEAT POST BOOT	
14.	1	30*60 SLEEVE	
15.	2	HANDLEBAR END CAP	
16.	2	FOAM GRIP	
17.	1	PEDAL (R)	
18.	1	PEDAL (L)	
19.	1	CHAIN COVER (R)	
20.	1	CHAIN COVER (L)	
21.	1	CHAIN COVER (F)	
22.	2	CRANK HOLE COVER	
23.	2	WHEEL	
24.	2	FOOT CAP	
25.	1 .	T-KNOB	
26.	1	KNOB	
27.	4	M8 SOCKET BOLT x 70mm	
28.	4	M8 SOCKET BOLT x 15mm	
29.	1	M5 SCREW x 25mm	
30.	2	M5 SCREW x 15mm	
31.	8	M8 WASHER	
32.	1	M8 SMALL WASHER	
33.	3	M8 SPRING WASHER	
34.	3	M8 NYLON NUT	
35.	4	M5 SCREW x 10mm	